EVOLUTION SERIES

Veneer Jamb - Non-Rated

J1400A

Double Rabbet Jamb (3/4")

- 1/32" wood veneer faces
- **2** 3/4" (19 mm) plywood veneer
- 3 1/32" hardwood backing
- 4 1/32" wood veneer faces
- 5 5/8" (15.8 mm) plywood veneer door stop
- **6** Doors
- Corner rabbet type

SPECIFICATIONS

MINIMUM WALL THICKNESS: 4 5/8" (117 mm)

ASSEMBLY: Please refer to installation instructions

MAXIMUM OPENING

| Single: 48" (1,219 mm) x 120" (3,048 mm)

Double: 96" (2,438 mm) x 120" (3,048 mm)

CASING: According to your needs

SHIPPING: Unassembled (Knock Down)

WRAPPING: Each frame will be shipped in a cardboard box, with 1/32" (1 mm) foam and

bundle wrapped.

Installation instructions and peel-and-stick door bumpers are included (mandatory)

WARRANTY: 3 years

OPTIONS

Other configurations upon request

* M.R. 5.1/5.2 according to project localisation. Contact us.

*** To get IEQ 4.4, specify NAUF jamb.

| Mounting brackets available

Pre-machining

Pre-finishing

| • Subject to evaluation. Contact us.

LEED Eligible Credits	MR					IEQ		ID 1	PR 2
	3	4	5	6	7	3.2	4.4	mode 2	
		~	*			0	***	0	0
		_					*****		







JAMB ASSEMBLY

Head and jamb





