

TRADITION SERIES

SOLID-WOOD JAMB – NON-RATED

J2300A

SINGLE RABBET JAMB (3/4")

- ① Hardwood
- ② Door
- ③ Corner rabbet type

SPECIFICATIONS

MINIMUM WALL THICKNESS: 3 5/8" (92 mm)

MINIMUM JAMB THICKNESS: 1 3/8" (35 mm)

ASSEMBLY: Please refer to installation instructions

MAXIMUM OPENING

| Single: 48" (1,219 mm) x 120" (3,048 mm)

| Double: 96" (2,438 mm) x 120" (3,048 mm)

NOTE: Dimensions limitations according to wood species.

CASING: According to your need

SHIPPING: Unassembled (Knock Down)

WRAPPING: Each frame will be shipped in a cardboard box, with 1/32" (1 mm) foam and bundle wrapped.

Installation instructions and peel-and-stick door bumpers are included (mandatory)

WARRANTY: 3 years

OPTIONS

| Other configurations upon request and availability

| * M.R. 5.1/5.2 according to project localisation. Contact us.

| ** To get M.R. 7.0, specify a FSC certified species.

| *** To get IEQ 4.4, specify NAUF jamb.

| Mounting brackets available


| Pre-machining

| Pre-finishing

| ○ Subject to evaluation. Contact us.

NOTE

| Mounting brackets are suggested for proper installation.



LEED Eligible Credits	MR					IEQ		ID 1	PR 2
	3	4	5	6	7	3.2	4.4	mode 2	
			*		**	○	***	○	○



FSC* certified products available on request.

JAMB ASSEMBLY

Head and jamb

