

TRADITION SERIES

SOLID-WOOD JAMB – RATED (20 MINUTES)

J2420A

DOUBLE RABBET JAMB (3/4")

- ① 3/4" (19 mm) hardwood
- ② 5/8" (15.8 mm) hardwood door stop
- ③ Doors
- ④ Corner rabbet type

SPECIFICATIONS

MINIMUM WALL THICKNESS: 4 9/16" (121 mm)

MINIMUM JAMB THICKNESS: 1 3/8" (35 mm)

ASSEMBLY: Please refer to installation instructions

MAXIMUM OPENING

- | Single: 48" (1,219 mm) x 108" (2,743 mm)
- | Double: 96" (2,438 mm) x 108" (2,743 mm)

CASING: 5/8" (15 mm) x 2 1/2" (64 mm)

SHIPPING: Unassembled (Knock Down)

WRAPPING: Each frame will be shipped in a cardboard box, with 1/32" (1 mm) foam and bundle wrapped.

Installation instructions and peel-and-stick door bumpers are included (mandatory)

WARRANTY: 3 years

OPTIONS

| Other configurations upon request and availability

| * M.R. 5.1/5.2 according to project localisation. Contact us.

| ** To get M.R. 7.0, specify a FSC certified species.

| *** To get IEQ 4.4, specify NAUF jamb.

| Mounting brackets available

| Pre-machining


| Pre-finishing

| ○ Subject to evaluation. Contact us.

NOTE


| Mounting brackets are suggested for proper installation.

| Installation requires a wood casing of 1/4" x 1 1/2" minimum.



JAMB ASSEMBLY

Head and jamb



LEED Eligible Credits	MR					IEQ		ID 1	PR 2
	3	4	5	6	7	3.2	4.4	mode 2	
		*		**		○	***	○	○



FSC* certified products available on request.