DOREX 700 SERIES

SIZED DOOR CLOSER

DOREX

The Dorex 700 series surface closer is recommended by door hardware specialists for use on a wide variety of residential and commercial applications with moderate traffic areas. Dorex brand products are recognized for value while delivering leading edge technology.



- Non handed
- Sized 1, 2, 3, 4 and 5
- · Universal retrofit hole spacing
- Power adjustable arm bracket
- Maximum 180° opening angle
- Tri-pack for regular, parallel arm and top jamb installation
- · Precision cast aluminum alloy housing
- Rack and pinion mechanism
- Non critical thermostatic valves
- High quality non gumming and non freezing hydraulic fluid
- Separate adjustable sweep and latching speed valves
- Optional adjustable back check control from 70° - 85°
- Finishes: metallic aluminum, dark bronze or sprayed gold
- cUL and UL listed
- 5 year limited warranty





DOREX 700 SERIES DOOR CLOSER

SPECIFICATION

Closers for interior and exterior doors shall be Dorex 700 series rack and pinion type with cast aluminum alloy shell. Closer shall be non-handed, surface mounted by 3/4" hole spacing and shall project no more than 3" from the door surface. Closer shall have two non-critical thermostatic valves to separately control sweep and latch speeds. Closer shall contain non-gumming and non-freezing hydraulic fluid to allow constant closing speeds under extreme temperatures. Brackets shall be supplied to permit regular, top jamb or parallel arm installation and standard arm bracket shall allow 15% power adjustment. Closer shall be supplied with all necessary mounting fastners. **OPTIONAL**: All Dorex 780 series closers shall have an independent adjustable valve to control backcheck cushioning to avoid uncontrolled door opening.

SELECTION GUIDE

CLOSER SIZE	DOOR TYPE	MAXIMUM DOOR WIDTH	DOOR WEIGHT RANGE	BACKCHECK	HOLD OPEN	DELAYED ACTION	BARRIER FREE	COVER
751	Interior	813mm (32")	15-36 kg (33-80 lbs)	N/A	N/A	N/A	N/A	N/A
	Exterior	N/A	13-30 kg (33-60 lbs)					
752	Interior	914mm (36")	25-45 kg (55-100 lbs)	N/A	N/A	N/A	N/A	N/A
	Exterior	813mm (32")	23-43 kg (33-100 lbs)					
753	Interior	1118mm (44")	40-66 kg (90-145 lbs)	N/A	N/A	N/A	N/A	N/A
	Exterior	914mm (36")	40-00 kg (90-143 lbs)					
754	Interior	1219mm (48")	57-86 kg (125-190 lbs)	784	N/A	N/A	N/A	N/A
	Exterior	1118mm (44")	37-80 kg (123-130 lbs)					
755	Interior	1321mm (52")	80-120 kg (175-265 lbs)	785	N/A	N/A	N/A	N/A
	Exterior	1219mm (48")	80-120 kg (173-203 lbs)					

SIZE CHART		CLOSER SIZE	751	752 / 753	754 / 755
0 0		А	165mm (6 1/2")	208mm (8 3/16")	230mm (9 1/16")
		В	181mm (7 1/8")	225mm (8 7/8")	248mm (9 3/4")
		С	19mm (3/4")		
E C D		D	43mm (1 11/16")	45mm	(1 3/4")
	├ F	Е	73mm (2 7/8")	83mm	(3 1/4")
		F	65mm (2 9/16")	73mm	(2 7/8")

PARTS & ACCESSORIES			CLOSER SIZE	DESCRIPTION		FINISH	PER CASE	WEIGHT (CASE)
DP 754	Drop pla	te	751			AL, BP, DU		17.0 kg
715 Parallel 735 Parallel		ırm bracket (sizes 2 & 3)	752	Regular, top jamb or parallel arm installation	AL, BP, DU	10	25.0 kg	
		irm bracket (sizes 4 & 5)	753		AL, BP, DU		25.0 kg	
SNB1420		oolt – for 1 3/4" door n bolt and machine screw)	754	- ann installation	AL, BP, DU	individually boxed	25.9 kg	
	(mioagi	bote and machine serewy	755		AL, DU		26.4 kg	
			784	As above with	AL, DU		26.8 kg	
			785	adjustable backcheck		AL, DU		26.8 kg
DP754		715	73	5	SNB1	420		
0 0 0						(