## **EVOLUTION SERIES**

Veneer Jamb – Non-Rated

## Flat Jamb (3/4")

- 1/32" wood veneer faces
- **2** 3/4" (19 mm) plywood veneer
- Hardwood backing
- 4 1/32" wood veneer face
- 6 Corner rabbet type

### SPECIFICATIONS

MINIMUM WALL THICKNESS: 2 1/2" (64 mm)

**ASSEMBLY:** Please refer to installation instructions

#### MAXIMUM OPENING

| Single: 48" (1,219 mm) x 120" (3,048 mm)

| Double: 96" (2,438 mm) x 120" (3,048 mm)

**CASING:** According to your needs

**SHIPPING:** Unassembled (Knock Down)

 $\ensuremath{\mathsf{WRAPPING:}}\xspace$  Each frame will be shipped in a cardboard box, with  $1/32''\,(1\mbox{ mm})$  foam and bundle wrapped.

Installation instructions and peel-and-stick door bumpers are included (mandatory)

#### WARRANTY: 3 years

#### OPTIONS

Other configurations upon request

\* M.R. 5.1/5.2 according to project localisation. Contact us.

| \*\*\* To get IEQ 4.4, specify NAUF jamb.

| Mounting brackets available

Pre-machining

Pre-finishing

OSubject to evaluation. Contact us.


#### NOTE

Rev. March 13, 2014

Mounting brackets are suggested for proper installation.

LEED	MR					IEQ		ID 1	PR 2
Eligible	З	4	5	6	7	3.2	4.4	mode 2	
Credits		$\checkmark$	*			0	***	0	0





3/4"

# J1100A

Variable

Baillargeon<sup>™</sup> | Toll Free: 1-800-804-5666 www.baillargeondoors.com