

Three Knuckle Standard Weight Series

The full mortise bearing hinge is recommended for standard weight, medium frequency doors, or doors with closing devices.

- Use for the common flush door/frame/wall application
- Decorative tips are available
- For available finishes see page 29

TA314
TA714




No.	ANSI Cross Reference	Base Material	Weight
TA314	A5112	Stainless	STD
TA314	A2112	Brass	STD
TA714	A8112	Steel	STD

Specifications

Inches	mm	Gauge	No. of Holes	Fasteners	
				Machine	Wood
3½ × 3½*	88.9 × 88.9	.123	6	½ × 10-24	1 × 10
4 × 4*	101.6 × 101.6	.130	8	½ × 12-24	1¼ × 12
4½ × 4	114.3 × 101.6	.134	8	½ × 12-24	1¼ × 12
4½ × 4½	114.3 × 114.3	.134	8	½ × 12-24	1¼ × 12
5 × 4½*	127 × 114.3	.146	8	½ × 12-24	1¼ × 12
5 × 5*	127 × 127	.146	8	½ × 12-24	1¼ × 12

* Not available in Brass Base material



Options:

Code	Description
NRP	Non-Removable Pin
ET	Exposed Tip
RC	Round Corner - ¼" radius furnished unless specified otherwise
HT	Hospital Tip
SSF	Safety Stud Feature
QC	ElectroLynx® Hinge - 2, 4, 6, 8, 10 or 12 wire available
CC	Concealed Circuit - 2, 4, 6, 8, 10 or 12 wire available
CC-18	Concealed Circuit - 2, 4, 6, 8 or 10 wire available (2-18AWG wires and the remainder 28AWG wires)
MM	Magnetic Monitoring